



## DESCAL RUST

Solvent for rust

### FEATURES

It is an ideal product for the rapid and complete removal of the rust that forms on ferrous surfaces.

With a selective action, it exclusively attacks the oxidized metal layer, leaving the non-oxidized part intact; furthermore, thanks to the presence of particular surfactants which lower the surface tension, high-wettable water-based solutions are formed which penetrate easily even in the most difficult access areas.

**DESCAL RUST** is recommended for the metalworking industry, for carpenters, for blacksmiths, plumbers and for anyone who has to remove the rust.

### CHEMICAL – PHYSICAL DATA

Physical state	: liquid
Color	: colorless
Solub. in water	: total
Density (15°C)	: 1,1 Kg/lt
pH <sub>(sol. 1%)</sub>	: 1
Flammability	: not flammable

### HOW TO USE

**DESCAL RUST** can be applied by immersion or by surface contact through the use of a brush or a cloth.

**For immersion.** Prepare a 25% aqueous solution (250 g per liter of water) Leave the pieces in immersion for 10-15 minutes.

At the end rinse thoroughly.

**For contact.** Apply the product as it is or a 50% aqueous solution (500 g per liter of water) according to the con-

sistency of the oxidized layer. Leave to act, repeat the treatment if necessary and rinse thoroughly.

**WARNINGS:** in order to avoid the formation of new rust on the manufactured articles it is advisable to apply the appropriate protective or anti-rust prod-

## DESCAL RUST P

Solvent for rust prefosfatation

ucts.

In this version, the product is specific as a pickling agent against rust on pieces in steel destined then to phosphating. It is used in the same way as the normal product.

Code: K0047420

### CHEMICAL – PHYSICAL DATA

Physical state	: liquid
Color	: colorless
Solub. in water	: total
Density (15°C)	: 1,4 Kg/lt
pH <sub>(sol. 1%)</sub>	: 1
Flammability	: not flammable