



VECTIS MOTOR

Engine lubricants

VECTIS MOTOR

It is a paraffinic oil with a high degree of refining and with additives that give it: a high viscosity index (SAE 15W50), good anti-wear and anti-corrosion properties, but above all a high detergent power that keeps the cylinders clean.

It can be classified as a SHPD oil (Super High Performance Diesel) which makes it suitable for diesel, turbo and aspirated engines, cars and trucks subject to heavy work (HD: Heavy Duty).

Its detergent power remains constant even at high temperatures and also in compressed turbo engines, it blocks the 'bore polish' phenomenon of the cylinder liners.

Its alkalinity reserve makes it possible to neutralize the sulfur acid derivatives formed during combustion.

SPECIFICATIONS	ACRONYM
API (American P.)	CE-CF-4/SG
US Military Specification	MIL-L-46152 E
CCMC (Comi)	D4-G4-PD2
MERCEDES BENZ	MB 228.1-MB 227.5
VOLVO	VDS
MAN	270/271
VOLKSWAGEN	VW 505/501
CATERPILLAR	CAT TO 2
ALLISON	C4

VECTIS TURBO

Multigrade oil with synthetic bases suitable for the lubrication of high performance diesel and petrol engines such as: turbochargers and volumetric compression.

Its performances are active even at low temperatures and with cold starts; it has a long service life, a good resistance to oxidation and a good detergent power. The presence of an anti-friction additive allows a 5% saving on fuel consumption. GRADE SAE 15W50.

The oil can be replaced after 20,000 Km.

SPECIFICATIONS	ACRONYM
API (American P.)	SG/CF-4
S US Military Specification	MIL-L-46152 E
CCMC (Comi)	D4-G4-PD2
MERCEDES BENZ	MB 228.1-MB 227.5
VOLVO	VDS
MAN	270/271
VOLKSWAGEN	VW 505/501
CATERPILLAR	CAT TO 2
ALLISON	C4

