



Rev. date: 19/06/12 Rev.: 2 DOPF-2

## **KEMPRO RAPID**

Quick dry anti-rust

### **FEATURES**

Quick dry anti-rust product containing zinc phosphate and alkyd resin. KEMPRO RAPID can be used as protective and anti-corrosive coat for indoors and outdoors.

- ✓ Quick drying. The painted part can be handled just after 10 minutes from the application, and the product completely dries in just three hours.
- ✓ Extreme adherence of the film to the support. If applied on clean and dry surfaces, it perfectly and permanently anchors to them.
- ✓ Cost effectiveness. 5 square metres of surface can be coated with a kilogram of product, with a thickness of 50 micron. For lower, more common thicknesses, 7-8 square metres can be coated with one kilogram of paint.

### **PHYSICAL- CHEMICAL DATA**

Specific weight: 1.7 +/- 0.1 Kg/lt  
Viscosity (FORD4): 180" (20°C)  
Yield (theoretical value): 9 square metres/kg  
(practical value): 7 square metres/ Kg  
Drying time  
Dry dust free: 10 minutes  
Dry to the touch: 30 minutes  
In depth: 3 hours  
Colours: different colours

### **METHODS OF USE**

Clean, degrease and dry the surfaces to treat accurately. Apply the product by spray or brush, diluting it in the indicated ratio, with a dilutant for synthetic surfaces.

BLACK – RAL 9011  
GREEN – RAL 6011  
GREY – RAL 7001  
RED- RAL 3009  
RED OXIDE – RAL 2009